

Measurements in millimeters				Measurements in inches			
ID (Inner diameter)mm	± (Tolerance)	W (Wire diameter)mm	± (Tolerance)	ID (Wire diameter)mm	± (Tolerance)	W (Wire diameter)mm	± (Tolerance)
1530	15.3	4	±0.10	60.236	0.602	0.157	0.004
1650	16.5	4	±0.10	64.961	0.650	0.157	0.004
1750	17.5	4	±0.10	68.898	0.689	0.157	0.004
1770	17.7	4	±0.10	69.685	0.697	0.157	0.004
1800	18	4	±0.10	70.866	0.709	0.157	0.004
420	4.2	5.33	±0.12	16.535	0.165	0.210	0.005
732	7.32	5.33	±0.12	28.819	0.288	0.210	0.005
780	7.8	5.33	±0.12	30.709	0.307	0.210	0.005
810	8.1	5.33	±0.12	31.890	0.319	0.210	0.005
892	8.92	5.33	±0.12	35.118	0.351	0.210	0.005
976	9.76	5.33	±0.12	38.425	0.384	0.210	0.005
1037	10.37	5.33	±0.12	40.827	0.408	0.210	0.005
1140	11.4	5.33	±0.12	44.882	0.449	0.210	0.005
1176	11.76	5.33	±0.12	46.299	0.463	0.210	0.005
1591	15.91	5.33	±0.12	62.638	0.626	0.210	0.005
1925	19.25	5.33	±0.12	75.787	0.758	0.210	0.005
2810	28.1	5.33	±0.12	110.630	1.106	0.210	0.005
1322	13.22	5.4	±0.12	52.047	0.520	0.213	0.005
1502	15.02	5.4	±0.12	59.134	0.591	0.213	0.005
658	6.58	5.6	±0.13	25.906	0.259	0.220	0.005
688	6.88	6	±0.15	27.087	0.271	0.236	0.006
1255	12.55	6	±0.15	49.409	0.494	0.236	0.006
1290	12.9	6	±0.15	50.787	0.508	0.236	0.006
1400	14	6	±0.15	55.118	0.551	0.236	0.006
2180	21.8	6	±0.15	85.827	0.858	0.236	0.006
745	7.45	6.99	±0.15	29.331	0.293	0.275	0.006
765	7.65	6.99	±0.15	30.118	0.301	0.275	0.006
790.4	7.904	6.99	±0.15	31.118	0.311	0.275	0.006
888	8.88	6.99	±0.15	34.961	0.350	0.275	0.006
1100	11	6.99	±0.15	43.307	0.433	0.275	0.006
1160	11.6	6.99	±0.15	45.669	0.457	0.275	0.006
1444	14.44	6.99	±0.15	56.850	0.569	0.275	0.006
1145	11.45	8	±0.15	45.079	0.451	0.315	0.006